Salvo Metal Works #307 Data Sheet

<u>Finial</u>

Part 1 General

1.1 SUMMARY

A. WORK INCLUDES:

1. Salvo Metal Works #307 Finial that attaches directly to the roof.

2. Coordinate with installation of the roof to assure proper location of snow guards.

3. Provide appropriate finial and fastening method for the roof

system.

B. RELATED SECTIONS:

- 1. Section 076000: Flashing and Sheet Metal. MasterFormatTM 2016 07 60 00
- 2. Section 072000: Roof Accessories. Mas

MasterFormatTM 2016 07 20 00

3. Section 077250: Fasteners

a. Finial

MasterFormatTM 2016 07 72 53

1.2 SYSTEM DESCRIPTION

A. COMPONENTS:

1. Salvo Metal Works #307 Finial system consists of an individual metal finial.

2. Fasteners:

A. Should be metal compatible with finial material.

B. Fasteners should be selected for compatibility with the roof deck.

C. Fastener strength should exceed or be equal to that of the finial system.

3. Mounting

A. See manufacturers mounting instructions.

B. DESIGN REQUIREMENTS:

1. Spacing to be recommended by manufacturer or architect.

2. Minimum 6 fasteners per finial.

3. It is important to design new structures or assess existing structures to ensure they can handle increased load.

1.3 SUBMITTAL

A. Product Data:

- 1. Manufacturer's specifications / standard drawing.
- 2. Installation instructions.

3. Recommended layout.

1.4 QUALITY ASSURANCE

A. Installer to be experienced in the installation of specified roofing material and finial.

B. Code Compliance:

Comply with all applicable local, state, federal, and international building codes and OSHA regulations as required.

1.5 DELIVERY / STORAGE / HANDLING

A. Inspect material upon delivery for any missing or defective items. Keep material dry, covered and protected until installed.

PART 2 - PRODUCTS

2.1 MANUFACTURER

A. Salvo Metal Works. 566 W 5th Ave, Naperville, IL 60563 www.SalvoMetalWorks.com (630)857-3631

2.2 MATERIALS

- Copper
- Lead-Coated Copper
- Copper Coated Stainless
- Freedom Grey
- Zinc
- Paint Grip or G90
- Aluminum

2.3 FINISH

- Copper 16 ounce and 20 ounce copper are available.
- Zinc Zinc is available in various shades of black or grey depending on metal supplier.
- Powder Coated finials may be powder coated by a painter.
- Paint paint grip or G90 may be painted by a painter.
- Kynar 500®, Hylar 5000®, PAC-CLAD® and other colored aluminums can be used.

PART 3 - EXECUTION

3.1 EXAMINATION

A. Substrate

 Inspect structure on which finial system is to be installed and verify that it will withstand any additional loading that it may incur. Notify general contractor of any deficiencies before installing Salvo Metal Works Finial.
Verify that roofing material is installed correctly while installing

Salvo Metal Works Finials.

3.2 INSTALLATION

- Comply with all architectural drawings and finial manufacturer's recommendations for location of system.
- Comply with manufacturer's written installation instructions for installation.
- Contact manufacturer for sample layouts if needed.